

PERFORMANCE SPECIFICATIONS

| Model | Heating Efficiency AFUE | Input Btuh Capacity [kW] | Output Btuh Capacity [kW] | Tons of add-on Cooling [kW] | Dimensions: HxWxD [inches] |
|--------------------|-------------------------|--------------------------|---------------------------|-----------------------------|----------------------------|
| G61MP | | | | | |
| G61MP-36B-045 | 94.10% | 44,000 (12.9) | 41,000 (12.0) | 2.5-3 (8.8-10.5) | 40 x 17-1/2 x 28-1/2 |
| G61MP-36B-070 | 94.10% | 66,000 (19.3) | 62,000 (18.2) | 2.5-3.5 (8.8-12.3) | 40 x 17-1/2 x 28-1/2 |
| G48MP-48C-090 | 94.10% | 88,000 (25.8) | 83,000 (24.3) | 3-4 (10.5-14.0) | 40 x 21 x 28-1/2 |
| G61MP-48C-110 | 94.10% | 110,000 (32.2) | 104,000 (30.5) | 3-4 (10.5-14.0) | 40 x 21 x 28-1/2 |
| G61MP-60C-090 | 94.10% | 88,000 (25.8) | 84,000 (24.6) | 4-5 (14.0-17.5) | 40 x 21 x 28-1/2 |
| G61MP-60C-110 | 94.10% | 110,000 (32.2) | 104,000 (30.5) | 4-5 (14.0-17.5) | 40 x 21 x 28-1/2 |
| G61MP-60D-135 | 94.10% | 132,000 (38.7) | 124,000 (36.3) | 4-5 (14.0-17.5) | 40 x 24-1/2 x 28-1/2 |
| G60DF/G60UH | | | | | |
| G60DF-36A-070X | 80.00% | 66,000 (19.3) | 54,000 (15.8) | 2-3 (7.0-10.6) | 40 x 14-1/2 x 28-1/2 |
| G60DF-36B-090 | 80.00% | 88,000 (25.8) | 72,000 (21.1) | 2-3 (7.0-10.6) | 40 x 17-1/2 x 28-1/2 |
| G60DF-48C-110 | 80.00% | 110,000 (32.2) | 90,000 (26.4) | 2.5-4 (8.8-14.1) | 40 x 21 x 28-1/2 |
| G60UH-24A-070 | 80.00% | 66,000 (19.3) | 54,000 (15.8) | 1.5-2 (5.3-7.0) | 40 x 14-1/2 x 28-1/2 |
| G60UH-36A-070X | 80.00% | 66,000 (19.3) | 54,000 (15.8) | 1.5-3 (5.3-10.6) | 40 x 14-1/2 x 28-1/2 |
| G60UH-36B-090 | 80.00% | 88,000 (25.8) | 72,000 (21.1) | 2-3 (7.0-10.6) | 40 x 17-1/2 x 28-1/2 |
| G60UH-36C-110 | 80.00% | 110,000 (32.2) | 90,000 (26.4) | 2-3 (7.0-10.6) | 40 x 21 x 28-1/2 |
| G60UH-48B-090X | 80.00% | 88,000 (25.8) | 72,000 (21.1) | 3-4 (10.6-14.1) | 40 x 17-1/2 x 28-1/2 |
| G60UH-60C-110X | 80.00% | 110,000 (32.2) | 90,000 (26.4) | 4-5 (14.0-17.6) | 40 x 21 x 28-1/2 |
| G60UH-60D-135 | 80.00% | 132,000 (38.7) | 108,000 (31.6) | 4-5 (14.0-17.6) | 40 x 24-1/2 x 28-1/2 |
| G51MP | | | | | |
| G51MP-24B-045 | 92.10% | 44,000 (12.9) | 41,000 (12.0) | 2-2.5 (7.0-8.8) | 40 x 17-1/2 x 28-1/2 |
| G51MP-36B-045 | 92.10% | 44,000 (12.9) | 41,000 (12.0) | 2-3 (8.8-10.5) | 40 x 17-1/2 x 28-1/2 |
| G51MP-36B-070 | 92.10% | 66,000 (19.3) | 62,000 (18.2) | 2-3 (8.8-10.5) | 40 x 17-1/2 x 28-1/2 |
| G51MP-36C-090 | 92.10% | 88,000 (25.8) | 82,000 (24.0) | 2-3 (8.8-10.5) | 40 x 21 x 28-1/2 |
| G51MP-48C-090 | 92.10% | 88,000 (25.8) | 82,000 (24.0) | 3-4 (10.5-14.0) | 40 x 21 x 28-1/2 |
| G51MP-48C-110 | 92.10% | 110,000 (32.2) | 103,000 (30.2) | 3-4 (10.5-14.0) | 40 x 21 x 28-1/2 |
| G51MP-60C-090 | 92.10% | 88,000 (25.8) | 82,000 (24.0) | 4-5 (14.0-17.5) | 40 x 21 x 28-1/2 |
| G51MP-60C-110 | 92.10% | 110,000 (32.2) | 103,000 (30.2) | 4-5 (14.0-17.5) | 40 x 21 x 28-1/2 |
| G51MP-60D-135 | 92.10% | 132,000 (38.7) | 123,000 (36.0) | 4-5 (14.0-17.5) | 40 x 24-1/2 x 28-1/2 |
| G50DF | | | | | |
| G50DF-24A-045X | 80.00% | 44,000 (12.9) | 36,000 (10.5) | 1.5-2 (5.3-7.0) | 40 x 14-1/2 x 28-1/2 |
| G50DF-36A-070X | 80.00% | 66,000 (19.3) | 53,000 (15.5) | 2-3 (7.0-10.6) | 40 x 14-1/2 x 28-1/2 |
| G50DF-36B-090 | 80.00% | 88,000 (25.8) | 71,000 (20.8) | 2-3 (7.0-10.6) | 40 x 17-1/2 x 28-1/2 |
| G50DF-48C-090X | 80.00% | 88,000 (25.8) | 71,000 (20.8) | 3-4 (10.6-14.1) | 40 x 21 x 28-1/2 |
| G50DF-48C-110 | 80.00% | 110,000 (32.2) | 89,000 (26.1) | 2-4 (7.0-14.1) | 40 x 21 x 28-1/2 |
| G50DF-60C-110 | 80.00% | 110,000 (32.2) | 90,000 (26.4) | 4-5 (14.1-17.6) | 40 x 21 x 28-1/2 |
| G50DF-60D-135 | 80.00% | 132,000 (38.7) | 107,000 (31.3) | 4-5 (14.1-17.6) | 40 x 24-1/2 x 28-1/2 |

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.

PERFORMANCE SPECIFICATIONS

| Model | Heating Efficiency AFUE | Input Btuh Capacity [kW] | Output Btuh Capacity [kW] | Tons of add-on Cooling [kW] | Dimensions: HxWxD [inches] |
|--------------------|-------------------------|--------------------------|---------------------------|-----------------------------|----------------------------|
| G50UH | | | | | |
| G50UH-24A-045X | 80.00% | 44,000 (12.9) | 35,000 (10.2) | 1.5-2 (5.3-7.0) | 40 x 14-1/2 x 28-1/2 |
| G50UH-24A-070 | 80.00% | 66,000 (19.3) | 54,000 (15.8) | 1.5-2.5 (5.3-8.8) | 40 x 14-1/2 x 28-1/2 |
| G50UH-36A-070X | 80.00% | 66,000 (19.3) | 53,000 (15.5) | 2-3 (7.0-10.6) | 40 x 14-1/2 x 28-1/2 |
| G50UH-36B-090 | 80.00% | 88,000 (25.8) | 71,000 (20.8) | 2-3 (7.0-10.6) | 40 x 17-1/2 x 28-1/2 |
| G50UH-36C-110 | 80.00% | 110,000 (32.2) | 88,000 (25.8) | 2-3 (7.0-10.6) | 40 x 21 x 28-1/2 |
| G50UH-48B-090X | 80.00% | 88,000 (25.8) | 71,000 (20.8) | 3-4 (10.6-14.1) | 40 x 17-1/2 x 28-1/2 |
| G50UH-48C-110 | 80.00% | 110,000 (32.2) | 87,000 (25.5) | 3-4 (10.6-14.1) | 40 x 21 x 28-1/2 |
| G50UH-48C-135 | 80.00% | 132,000 (38.7) | 106,000 (31.0) | 2-4 (7.0-14.1) | 40 x 21 x 28-1/2 |
| G50UH-60C-110 | 80.00% | 110,000 (32.2) | 88,000 (25.8) | 4-5 (14.0-17.6) | 40 x 21 x 28-1/2 |
| G50UH-60D-135 | 80.00% | 132,000 (38.7) | 107,000 (31.3) | 4-5 (14.0-17.6) | 40 x 24-1/2 x 28-1/2 |
| G50UH-60D-155 | 80.00% | 154,000 (45.1) | 122,000 (35.7) | 4-5 (14.0-17.6) | 40 x 24-1/2 x 28-1/2 |
| G43UF | | | | | |
| G43UF-24B-045 | 92.10% | 44,000 (12.9) | 40,300 (11.8) | 1.5-2 (5.3-7.0) | 40 x 17-1/2 x 28-1/2 |
| G43UF-24B-070 | 90.00% | 66,000 (19.3) | 61,000 (17.9) | 1.5-2 (5.3-7.0) | 40 x 17-1/2 x 28-1/2 |
| G43UF-36B-070 | 92.10% | 66,000 (19.3) | 62,000 (18.2) | 2-3 (8.8-10.5) | 40 x 17-1/2 x 28-1/2 |
| G43UF-36C-090 | 92.10% | 88,000 (25.8) | 82,000 (24.0) | 2-3 (7.0-10.5) | 40 x 21 x 28-1/2 |
| G43UF-36C-090H | 90.00% | 88,000 (25.8) | 81,000 (23.7) | 2-3 (7.0-10.5) | 40 x 21 x 28-1/2 |
| G43UF-48C-090 | 92.10% | 88,000 (25.8) | 82,000 (24.0) | 3-4 (10.5-14.0) | 40 x 21 x 28-1/2 |
| G43UF-48C-110 | 92.10% | 110,000 (32.2) | 103,000 (30.2) | 3-4 (10.5-14.0) | 40 x 21 x 28-1/2 |
| G43UF-48C-110H | 90.00% | 110,000 (32.2) | 101,000 (29.6) | 3-4 (10.5-14.0) | 40 x 21 x 28-1/2 |
| G43UF-60C-110 | 92.10% | 110,000 (32.2) | 103,000 (30.2) | 4-5 (14.0-17.5) | 40 x 21 x 28-1/2 |
| G43UF-60D-135 | 92.10% | 132,000 (38.7) | 123,000 (36.0) | 4-5 (14.0-17.5) | 40 x 24-1/2 x 28-1/2 |
| G40DF/G40UH | | | | | |
| G40DF-24A-045X | 80.00% | 44,000 (12.9) | 36,000 (10.5) | 1.5-2 (5.3-7.0) | 40 x 14-1/2 x 28-1/2 |
| G40DF-36A-045 | 80.00% | 44,000 (12.9) | 35,000 (10.3) | 2-3 (7.0-10.6) | 40 x 14 1/2 x 28 1/2 |
| G40DF-36A-070X | 80.00% | 66,000 (19.3) | 53,000 (15.5) | 2-3 (7.0-10.6) | 40 x 14-1/2 x 28-1/2 |
| G40DF-36B-090 | 80.00% | 88,000 (25.8) | 71,000 (15.5) | 2-3 (7.0-10.6) | 40 x 17-1/2 x 28-1/2 |
| G40DF-48B-070 | 80.00% | 66,000 (19.3) | 53,000 (15.5) | 3-4 (10.6-14.1) | 40 x 17 1/2 x 28 1/2 |
| G40DF-48C-090X | 80.00% | 88,000 (25.8) | 71,000 (15.5) | 3-4 (10.6-14.1) | 40 x 21 x 28-1/2 |
| G40DF-48C-110X | 80.00% | 110,000 (32.2) | 89,000 (26.1) | 2.5-4 (8.8-14.1) | 40 x 21 x 28-1/2 |
| G40DF-60C-110X | 80.00% | 110,000 (32.2) | 90,000 (26.4) | 4-5 (14.1-17.6) | 40 x 21 x 28-1/2 |
| G40DF-60D-135 | 80.00% | 132,000 (38.7) | 107,000 (31.3) | 4-5 (14.1-17.6) | 40 x 24-1/2 x 28-1/2 |
| G40UH-24A-045X | 80.00% | 44,000 (12.9) | 36,000 (10.5) | 1.5-2 (5.8-7.0) | 40 x 14-1/2 x 28-1/2 |
| G40UH-24A-070 | 80.00% | 66,000 (19.3) | 54,100 (15.6) | 1.5-2 (5.8-7.0) | 40 x 14-1/2 x 28-1/2 |
| G40UH-36A-045 | 80.00% | 44,000 (12.9) | 35,900 (10.5) | 2-3 (7.0-10.6) | 40 x 14 1/2 x 28 1/2 |
| G40UH-36A-070X | 80.00% | 66,000 (19.3) | 54,100 (15.6) | 2-3 (7.0-10.6) | 40 x 14-1/2 x 28-1/2 |
| G40UH-36B-090 | 80.00% | 88,000 (25.8) | 72,100 (21.1) | 2-3 (7.0-10.6) | 40 x 17-1/2 x 28-1/2 |
| G40UH-36C-110 | 80.00% | 110,000 (32.2) | 90,200 (26.4) | 2-3 (7.0-10.6) | 40 x 21 x 28-1/2 |
| G40UH-48B-070 | 80.00% | 66,000 (19.3) | 54,100 (15.6) | 2-4 (7.0-14.1) | 40 x 17 1/2 x 28 1/2 |
| G40UH-48B-090X | 80.00% | 88,000 (25.8) | 72,100 (21.1) | 3-4 (10.6-14.1) | 40 x 17-1/2 x 28-1/2 |
| G40UH-48C-110 | 80.00% | 110,000 (32.2) | 88,500 (25.9) | 3-4 (10.6-14.1) | 40 x 21 x 28-1/2 |
| G40UH-48C-135 | 80.00% | 132,000 (38.7) | 106,900 (31.3) | 2.5-4 (8.8-14.1) | 40 x 21 x 28-1/2 |
| G40UH-60C-110X | 80.00% | 110,000 (32.2) | 89,400 (26.2) | 4-5 (14.1-17.6) | 40 x 21 x 28-1/2 |
| G40UH-60D-135 | 80.00% | 132,000 (38.7) | 106,900 (31.3) | 4-5 (14.1-17.6) | 40 x 24-1/2 x 28-1/2 |
| G40UH-60D-155 | 80.00% | 154,000 (45.1) | 124,700 (36.5) | 4-5 (14.1-17.6) | 40 x 24-1/2 x 28-1/2 |

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change. Low-NOx units (labeled "X" in the model number) meet California Nitrogen Oxides standards.