

# LANDMARK™ ROOFTOP UNIT PERFORMANCE SPECIFICATIONS

	Nom. Ton	Model	COOLING DATA					HEATING INPUT				AIRFLOW RANGE				PHYSICAL DATA	
			Gross Cap. [Btu/h]	ARI Rated Net Cap. [Btu/h]	ARI Rated CFM	Seasonal Efficiency [SEER]	Full Load [EER]	Low	Standard	Medium	High	Minimum Cooling	Minimum Heating	Max.	Static [in wc]	Dimensions H x W x L [inches]	Ship Wt. [lbs.]
GAS/ELECTRIC UNITS	2	KGA024S4D	24,400	23,600	840	13.00	11.4	—	65,000	—	—	560	740	960	0-0.9	39 x 47 x 87-1/4	591
	2.5	KGA030S4D	29,800	28,800	1000	13.00	11.2	—	65,000	—	—	700	740	1200	0-0.9	39 x 47 x 87-1/4	593
	3	KGA036S4D	37,500	36,000	1200	13.00	10.7	—	65,000	105,000	—	840	960-1040	1440	0-0.9	39 x 47 x 87-1/4	594
	4	KGA048S4D	50,000	48,000	1600	13.00	11.0	—	65,000	105,000	150,000	1120	960-1040	1920	0-0.9	39 x 47 x 87-1/4	631
	5	KGA060S4D	61,800	59,000	1800	13.00	11.2	—	65,000	105,000	150,000	1400	960-1300	2400	0-0.9	39 x 47 x 87-1/4	661
	6	KGA072S4B	72,800	70,000	2100	—	11.0	—	65,000	105,000	150,000	1680	960-1300	2880	0.1-1.5	47 x 47 x 87-1/4	760
KW Range*																	
ELECTRIC/ELECTRIC UNITS	2	KCA024S4D	24,400	23,600	840	13.00	11.4	7.50	10.00	—	—	560	640	960	0-0.9	39 x 47 x 87-1/4	555
	2.5	KCA030S4D	29,800	28,800	1000	13.00	11.2	7.50	10.00	—	—	700	800	1200	0-0.9	39 x 47 x 87-1/4	557
	3	KCA036S4D	37,500	36,000	1200	13.00	10.7	7.50	15.00	—	—	840	960	1440	0-0.9	39 x 47 x 87-1/4	558
	4	KCA048S4D	50,000	48,000	1600	13.00	11.0	7.50	15.00	22.50	—	1120	960	1920	0-0.9	39 x 47 x 87-1/4	595
	5	KCA060S4D	61,800	59,000	1800	13.00	11.2	7.50	15.00	22.50	—	1400	1600	2400	0-0.9	39 x 47 x 87-1/4	625
	6	KCA072S4B	72,800	70,000	2100	—	11.2	7.50	15.00	22.50	30.00	1680	1920	2880	0.1-1.5	47 x 47 x 87-1/4	724
								47 Cap.	HSPF/COP 47	17 Cap.	COP 17						
HEAT PUMP UNITS	2	KHA024S4D	23,600	22,800	800	13.00	11.2	24,000	7.7/3.4	14,400	2.3	560	640	960	0-0.9	39 x 47 x 87-1/4	591
	2.5	KHA030S4D	30,000	29,000	1000	13.00	11.3	29,200	7.7/3.5	17,600	2.3	700	800	1200	0-0.9	39 x 47 x 87-1/4	593
	3	KHA036S4D	37,100	35,600	1160	13.00	10.9	36,400	7.7/3.6	22,000	2.3	840	960	1440	0-0.9	39 x 47 x 87-1/4	595
	4	KHA048S4D	49,000	47,000	1600	13.00	10.7	48,000	7.7/3.5	29,500	2.4	1120	960	1920	0-0.9	39 x 47 x 87-1/4	617
	5	KHA060S4B	61,500	59,000	1985	13.00	10.9	60,500	7.7/3.6	36,000	2.4	1400	1600	2400	0.1-1.5	39 x 47 x 87-1/4	727

Certified in accordance with the USE certification program which is based on ARI Standard 210/240 (5 tons and below): 95°F outdoor air temperature and 80°F db/67°F wb entering evaporator coil air.

Certified in accordance with the ULE certification program which is based on ARI standard 340/360 (6 tons and over): 95°F outdoor air temperature and 80°F db/67°F wb entering evaporator air; minimum external duct static pressure.

Direct drive blower motors available for 2- to 5-ton models.

\*Nominal electric heat capacities are rated at 240V, 480V and 600V.

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.