

TSA/TPA AIR CONDITIONER AND HEAT PUMP PERFORMANCE SPECIFICATIONS

			COOLING DATA ^{2, 3}		HEATING DATA ^{4, 5}				PHYSICAL DATA		
	Nominal Tonnage	Model	Sound Rating dB ¹	ARI Rated Cap. [Btuh]	Efficiency [EER]	Capacity [Btuh]	17F COP	Capacity [Btuh]	47F COP	Dimensions H x W x L [inches]	Ship Wt. [lbs.]
	AIR CONDITIONERS	6	TSA072S4S	81	71,000	11.20	—	—	—	—	48.75 x 39.875 x 48.375
7.5		TSA090S4S	81	89,000	11.20	—	—	—	—	48.75 x 39.875 x 48.375	367
10		TSA120S4S	86	113,000	11.20	—	—	—	—	48.75 x 43.625 x 60.125	477
10		TSA120S4D	85	115,000	11.20	—	—	—	—	48.75 x 43.625 x 60.125	505
12.5		TSA150S4D	86	136,000	11.00	—	—	—	—	48.75 x 43.625 x 60.125	538
15		TSA180S4D	88	178,000	11.00	—	—	—	—	48.75 x 88.75 x 60.125	860
20		TSA240S4D	89	232,000	11.00	—	—	—	—	48.75 x 88.75 x 60.125	950
HEAT PUMPS	7.5	TPA090S4S	85	89,000	11.00	50,000	2.20	88,000	3.30	48.75 x 43.625 x 60.125	435
	10	TPA120S4S	86	112,000	11.00	70,000	2.20	116,000	3.30	48.75 x 43.625 x 60.125	515

¹Sound rating number in accordance with test conditions included in ARI Standard 270.

²6-ton-and-over equipment certified in accordance with ULE certification program, which is based on ARI Standard 340/360.

³Cooling ratings, 95°F (35°C) outdoor air temperature and 80°F (27°C) db/67°F (19°C) wb entering indoor coil air.

⁴High-temperature heating ratings, 47°F (8°C) db/43°F (6°C) wb outdoor air temperature and 70°F (21°C) entering indoor coil air.

⁵Low-temperature heating ratings, 17°F (-8°C) db/15°F (-9°C) wb outdoor air temperature and 70°F (21°C) entering indoor coil air.

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.

